
14
PCI BUS
24a
AD[31:0]
16
38
16a
PCI Bus INTF.
AND CSRs
24
26a
SDRAM
16a
Mbus[63:0]
MEMORY UNIT
Fbus/PCI/AMBA
32
PROCESSOR
Core, 20
Mbus[63:0]
AMBA[31:0]
16b
30
26b
SRAM UNIT
Fbus/AMBA
SRAM
16b
SRBus[63:0]
Amba Xlator
34
22C
16c
Fbus
INTERFACE
R/TFIFOs
SCRATCH
CSRs
28
FLASHROM
22a
MICROENGINES, 22
FBUS[63:0]
12
10
18
10/100BaseT
Octal MAC
GIGABIT
ETHERNET
13a
13b

FIG. 1

FIG. 2-1

FIG. 2-2

FIG. 2




16b
SDRAM
2MB TO 64MB
32
BOOT/FLASH
UP TO 6MB
16c
SDRAM
INTER
PUSH
POP
CAM
38
Hi-priority
AddQ
READQ
AddQ
ORDERQ
AddQ
lockFall
AddQ
AMBA
AddQ_1
ARBITER
60
34
F0 BOX
F1 BOX
F2 BOX
F3 BOX
F4 BOX
F5 BOX
22a
22F
HASH
29c
RcPdc
29a
TrPdc
29b
SCRATCH PAD
29
Rbus INTERFACE LOGIC
TIME SLOT CONTROLLER
28
26b
F Bus - 64bit @ 66Mhz
18
3/17

FIG. 2-2


AMBA[31:0]
MBUS[31:0]
SBUS[31:0]
22f
XReg$
32 SDRAM Regs
32 SDRAM/Ambs
8 EACH/CONTEXT
32 SDRAM Regs
32 SDRAM/Ambs
GReg$
64 A GPRs
64 B GPRs
16 A, 16 B
PER CONTEXT
80
wrA wrB
RD
TRANSFER
REGS
rd
74
SEQ#_event_response
FBI_event_response
sram_event_response
sdram_event_response
amba_event_response
CONTEXT
EVENT
ARBITER
78
rds
rdb
WRITE
TRANSFER REGS
72b
UENGINE CONTROLLER
72c
uPC_1
uPC_2
uPC_3
uPC_4
73
DECODE
72
GENERAL
PURPOSE
REGISTERS
A
B
W
76b
72a
IMMEDIATE_DATA
ADDRESS
CONTROL STORE
1024 WORDS
32bit WORDS
70
A
B
76a
SHIFTER
ALU
WRITE
76

FIG. 3


82a, LOOKUP MICROINSTRUCTIONS
82b, FORM REGISTER FILE ADDRESSES
82c, FETCH OPERANDS
82d, ALU OPERATION
82e, WRITE-BACK OF RESULTS

FIG. 4

branch instructions:



defbr: A value of 0, 1 or 2 may be specified. If non-zero, the value indicates the the following 1 or 2 micowords will be allowed to execute before the branch operation takes place.

gb: If set, guess that the branch path will be taken, thus prefetch the branch microword address. Otherwise prefetch the non-branch path. This field is only allowed to be set when defbr=0 or defbr=1.

branch address: branch address conditionally or unconditionally selected.

br_mask: Is decoded to the following options:

1) unconditional branch
2) branch when ALU<31>=1 (<0)
3) branch when ALU<31>=0 (>=0)
4) branch when ALU<31>=1 OR ALU<31:0>=0 (<=0)
5) branch when ALU<31>=0 AND ALU<31:0>!=0 (>0)
6) branch when ALU<31:0>=0 (=0)
7) branch when ALU<31:0>=1 (!=0)
8) branch when specified context mask = current context
9) branch when specified context mask ! = current context
10) branch on carry-out set
11) branch on carry-out clear
15) look at extended branch field to further decode branch type

extend_br: branches on various context-swapping signals or other signals

evpip: indicates pipe stage that this branch should be evaluated in

c msk: specifies a context number with which to conditionally branch on.

branch cmd: further specifies the type of branch, e.g., looks at condition codes of some other branch criteria

FIG. 5A



Context Descriptors:

1) Wake-up Events

0 = kill	8 = FBI	128 = SEQ_NUM_LSB
1 = voluntary	16 = INTER_THREAD	
2 = SRAM	32 = PCI_DMA_1	
4 = SDRAM	64 = PCI_DMA_2	

2) db → branch defer amount

3) va → value of sequence number

FIG. 5B



FIG. 6

FIG. 7-1

FIG. 7-2

FIG. 7




REMOVE QUEUE ARBERATION
INSERT QUEUE CONTROL
3
BANK ORDER ORDERQ HI PRIORITY
F0, F1, F2,F3, F4, F5, and - PCI bus data pull_wr/push_rd engine
97
12
6
F0_in_data_h[63:0]
F0_out_data_h[63:0]
F1_in_data_h[63:0]
F1_out_data_h[63:0]
F2_in_data_h[63:0]
F2_out_data_h[63:0]
F3_in_data_h[63:0]
F3_out_data_h[63:0]
F4_in_data_h[63:0]
F4_out_data_h[63:0]
F5_in_data_h[63:0]
F5_out_data_h[63:0]
Fbox_wr_req_and_wc_bus
Fbox_rd_valid_and_dst_bus
PCI_wr_req_and_wc_bus
PCI_rd_valid_and_dst_bus

FIG. 7-2


SDRAM ARBITRATION SCHEME
CHAINED Fbox REQUESTS
115a
MORE CHAINED?
YES
115b
NO
ARM SYSTEM BUS REQUESTS
MORE ARM?
YES
NO
PCI REQUESTS
MORE PCT?
YES
115c
NO
MORE ARM?
YES
NO
115d
HIGH PRIORITY QUEUE SERVICE
YES
CHAINED?
NO
115e
OPPOSITE BANK REQUESTS
YES
CHAINED?
NO
115f
ORDER BANK REQUESTS
YES
CHAINED?
NO
115g
SAME BANK REQUESTS

FIG. 7A

SINGLE QUADWORD WRITE FOLLOWED BY A SINGLE QUADWORD READ

WITHOUT ACTIVIE MEMORY OPTIMIZATION



WITH ACTIVIE MEMORY OPTIMIZATION



WHERE Trcd = RAS to CAS delay

Tdpl = DATA Input to Precharge Delay

Trp = Time to Precharge

FIG. 7B

FIG. 8-1

FIG. 8-2

FIG. 8

FIG. 8-1



13/17


REMOVE QUEUE ARBIRIATION
INSERT QUEUE CONTROL
rd_fall
F0, F1, F2,F3, F4, F5, and - PCI bus data pull_wr/push_rd engine
127
12
F0_in_data_h[63:0]
F0_out_data_h[63:0]
F1_in_data_h[63:0]
F1_out_data_h[63:0]
F2_in_data_h[63:0]
F2_out_data_h[63:0]
F3_in_data_h[63:0]
F3_out_data_h[63:0]
F4_in_data_h[63:0]
F4_out_data_h[63:0]
F5_in_data_h[63:0]
F5_out_data_h[63:0]
Fbox_wr_req_and_wc_bus
Fbox_rd_valid_and_dst_bus
NOTE: ADDRESS: 22bits
COMMENT: 4bits
Src/Dat: 6bits
SUPPORTED COMMENTS:
READ 1 QUADWORD
READ n QUADWORD
WRITE 1 QUADWORD
WRITE n QUADWORD
READLOCK
WRITEUNLOCK
UNLOCK
RESERVE n LOCKS
INSERT QUEUE ELEMENTS
REMOVE QUEUE ELEMENTS

FIG. 8-2



10 CYCLES VS. 14.

FIG. 8A



FIG. 9-1

FIG. 9-1

FIG. 9-2

FIG. 9



17/17

ATU NOTES:
a) CORE TO FBoxRegs:
USE aram_push_data_bus

b) CORE TO FBI Regs:
USE PRIVATE ATU/FBI
cmd/data bus

c) CORE READS FBoxRegs:
USE Sram_pull_data_bus

d) CORE READS FBI Regs:
USE sram_push_data_bus
(UNLESS sram APPEAR FAKE
ANOTHER Fbox To FBI ON
sram_push_bus)

Card_Req_R,2:0>
000 NONE
001 Sram Chain
010 SDR Chain
011 Sram
100 SDR
101 FBI
110 PCI
111

Tx_CMD_drv_en_R<1:0>
0 NONE
1 GRANT

Sdram_puXX_addr_R<6:0>
[4:0] xfer_reg_addr
IF NOT TFIFO
[6:0] TIFIFO_addr

Sdram_puXX_ID_R<6:0>
0 - 5 Fboxes
8 - 13 Fboxes-csr
6 fbl
15 nop

Sdram_puXX_addr_R<6:0>
[4:0] xfer_reg_addr

Sdram_puXX_ID_R<6:0>
0 - 5 Fboxes
8 - 13 Fboxes-csr
6 fbl
15 nop

Fbox BRANCH/Ctx CHOICES

1) FBI_adone		br / ctx
2) FBI_auto_push		br / ctx
3) Ithread_adone		br / ctx
4) signal_rec_cxt		br / ctx
5) Seq#1_change	(flag)	br / ctx
6) Seq#2_change	(flag)	br / ctx
7) SRAM_adone		br / ctx
8) SDRAM_adone		br / ctx
9) volunteer_ctx_swap		ctx
10) Req_req_avaliable	(flag)	br
11) SDRAM rd parity err		br
12) Fbox_push_protect	(flag)	br
13) ccodes, contexts and kill		

FIG. 9-2